

C BIO FOAM-S D[®]

Strong alkaline foaming cleaner for heavy contaminated equipment

Product description

BIO FOAM-S is a strong alkaline foaming product to clean smoking cabinets and heavy contaminated equipment. Thanks to its composition it is also suitable for use in not heated smoking cabinets.

Properties

BIO FOAM-S is based on non-ionic surfactants, sodium hydroxide, potassium hydroxide, complexing agent and wetting agents.

BIO FOAM-S is especially formulated for the removal of grease, smoke, tar and sugars, ... on place to be used in a foaming device (manual or automatic) and therefore very suitable for: smoking cabinets, trolleys, industrial deep fryers and strongly contaminated equipment, tables and surfaces of cutting plants, etc.

Directions for use


Dilute **BIO FOAM-S** to proportions of 2 – 5 %.
Apply with a dosing system and let it act upon during 10 to 30 minutes.
Rinse with warm or cold water (high or low pressure).

Specifications

Appearance:	clear dark brown liquid
pH (1%):	12.0-13.0
Density (20°C):	1.350 kg/l
Freezing point:	-10°C

Corrosion data and -precautions

Never mix with an acid !
Please check the MSDS.



Test method

Reagents:	0.05M HCl solution Phenolphthalein Indicator
Procedure:	Add to 100ml water 5ml test solution and 2-3 drops of the Indicator. Titrate with the HCl solution to a permanent pink end point.
Calculation:	% BIO FOAM-S = titre (ml) / 5.7