

< DM FOAM-S+ >

strong alkaline foaming cleaner for smoking cabinets

Product description

DM FOAM-S+ is a strong alkaline foaming product to clean smoking cabinets and heavy contaminated equipment.

Properties

DM FOAM-S+ is based on sugar surfactants, sodium hydroxide, NTA and wetting agents.

DM FOAM-S+ is especially formulated for the removal of grease, smoke, tar and sugars, ... on place to be used in a foaming device and therefore very suitable for: smoking cabinets, industrial deep fryers and strongly contaminated equipment.

Directions for use

Dilute **DM FOAM-S+** to proportions of 2 – 5 %.

Apply under high pressure and let it act upon during 20 minutes.

Rinse with clean water under high pressure; in case of very fatty conditions: rinse with warm water.

Specifications

Appearance:	dark brown liquid
pH (1%):	12.0
Density (20°C):	1.225 kg/l
Freezing point:	-10°C

Corrosion data and -precautions

Never mix with an acid !
Please check the MSDS.



Test method

Reagents:	0.05M HCl solution Phenolphthalein Indicator
Procedure:	Add to 100ml water 5ml test solution and 2-3 drops of the Indicator. Titrate with the HCl solution to a permanent pink end point.
Calculation:	% DM FOAM-S+ = titre (ml) / 5.7