

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Product name : Cid 2000 Pro
 Product code : H45
 Product group : Cleaning product.

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use
 Use of the substance/mixture : See product bulletin for detailed information

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

CID LINES NV
 Waterpoortstraat, 2
 B-8900 Ieper - Belgique
 T + 32 57 21 78 77 - F +32 57 21 78 79
sds@cidlines.com - <http://www.cidlines.com>

Importer

Best Veterinary Solutions, Inc
 1716 Detroit St
 P.O. Box 370
 IA 50075 Ellsworth - United States of America
 T 888-378-4045
<https://www.bestvetsolutions.com/>

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
Australia	Poisons Information Centre		13 11 26	
Belgium	Centre Anti-Poisons/Antigifcentrum c/o Hôpital Central de la Base - Reine Astrid	Rue Bruyn B -1120 Brussels	+32 70 245 245	
Canada	CANUTEC Country Organization/Company Address Emergency number Comment		(613) 996-6666	
Finland	Poison Information Centre	P.O.B 790 (Tukholmankatu 17) HUS SF - 00029 Helsinki	+358 9 471 977	
Iceland	Eitrunarmiðstöð Landspítali	Fossvogi 108 Reykjavik	+354 543 22 22	
Malta	Medicines & Poisons Info Office	Mater Dei Hospital MSD Msida	112	
Netherlands	Nationaal Vergiftigingen Informatie Centrum Uitsluitend bestemd om artsen te informeren bij accidentele vergiftigingen	Huispostnummer B.00.118, PO Box 85500 3508 GA Utrecht	+31 30 274 88 88	
New Zealand	The National Poisons Centre	University of Otago, 2nd Floor, Adams Building, 18 Frederick Street, 9016 Dunedin	0800 764 766 0800 POISON	
Switzerland	Centre Suisse d'Information Toxicologique Swiss Toxicological Information Centre, Schweizerisches Toxicologisches Informationszentrum STIZ	Freiestrasse 16 Postfach CH-8032 Zurich	+41 44 251 51 51 (International) 145 (National)	

Cid 2000 Pro

Safety Data Sheet

According to OSHA 29 CFR 1910.1200

United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER London	+44 20 7188 7188	
USA	American Association of Poison Control Centers		1-800-222-1222	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Labelling according to OSHA 29 CFR 1910.1200

Organic Peroxides, Type D	H242
Acute toxicity (oral), Category 4	H302
Acute toxicity (inhal.), Category 4	H332
Skin corrosion/irritation, Category 1A	H314
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation	H335
Hazardous to the aquatic environment — Chronic Hazard, Category 1	H410

Full text of H statements : see section 16


Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to OSHA 29 CFR 1910.1200

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Hazard statements (CLP)

: H242 - Heating may cause a fire.
H302+H332 - Harmful if swallowed or if inhaled.
H314 - Causes severe skin burns and eye damage.
H335 - May cause respiratory irritation.
H410 - Very toxic to aquatic life with long lasting effects.

Precautionary statements (CLP)

: P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P260 - Do not breathe dust/fume/gas/mist/vapours/spray.
P221 - Take any precaution to avoid mixing with combustibles...
P304+P340 - IF INHALED Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER/doctor. Specific treatment is urgent.
P301+P330+P331+P310+P321 - IF SWALLOWED Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER/doctor. Specific treatment.
P303+P361+P353 - IF ON SKIN (or hair) Take off immediately all contaminated clothing. Rinse skin with water/shower.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrogen peroxide	(CAS-No.) 7722-84-1 (EC-No.) 231-765-0 (EC Index-No.) 8-003-00-9 (REACH-no) 01-2119485845-22	15 – 30	Ox. Liq. 1, H271 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1A, H314 STOT SE 3, H335 Aquatic Chronic 3, H412

Cid 2000 Pro

Safety Data Sheet

According to OSHA 29 CFR 1910.1200

Peracetic acid	(CAS-No.) 79-21-0 (EC-No.) 201-186-8 (EC Index-No.) 607-094-00-8 (REACH-no) 01-2119531330-56	5 – 15	Flam. Liq. 3, H226 Org. Perox. D, H242 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1A, H314 STOT SE 3, H335 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Acetic acid	(CAS-No.) 64-19-7 (EC-No.) 200-580-7 (EC Index-No.) 607-002-00-6 (REACH-no) 01-2119475328-30	5 – 15	Flam. Liq. 3, H226 Skin Corr. 1A, H314

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Seek medical attention immediately.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Seek medical advice (show the label where possible).
First-aid measures after eye contact	: Rinse immediately with plenty of water. Seek medical attention immediately.
First-aid measures after ingestion	: IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER/doctor.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Inhalation of vapour can cause breathing difficulties. Cough. Sore throat.
Symptoms/effects after skin contact	: Redness, pain. Causes severe skin burns and eye damage.
Symptoms/effects after eye contact	: Redness, pain. Blurred vision. Tears. Serious damage to eyes.
Symptoms/effects after ingestion	: Burning sensation. Cough. Cramps. May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. Swallowing a small quantity of this material will result in serious health hazard.

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : All extinguishing media allowed.

5.2. Special hazards arising from the substance or mixture

Fire hazard : May cause fire. Oxidizing.

5.3. Advice for firefighters

Precautionary measures fire	: Wear fire/flare resistant/retardant clothing. Eliminate all ignition sources if safe to do so.
Firefighting instructions	: Use water spray or fog for cooling exposed containers.
Protection during firefighting	: Exercise caution when fighting any chemical fire. Do not enter fire area without proper protective equipment, including respiratory protection. Wear fire/flare resistant/retardant clothing. Heat resistant gloves.
Other information	: On exposure to high temperature, may decompose, releasing toxic gases.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Spill should be handled by trained cleaning personnel properly equipped with respiratory and eye protection. Stop leak if safe to do so. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	: Stop leak without risks if possible. Collect spillage. Use suitable disposal containers.
Methods for cleaning up	: Clean up any spills as soon as possible, using an absorbent material to collect it.

6.4. Reference to other sections

No additional information available

Cid 2000 Pro

Safety Data Sheet

According to OSHA 29 CFR 1910.1200

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : When handling product, avoid contact with skin and eyes. Wear personal protective equipment. Do not breathe vapour/aerosol. Provide good ventilation in process area to prevent formation of vapour.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in dry, cool, well-ventilated area. Provide local exhaust or general room ventilation to minimize dust and/or vapour concentrations. Keep container closed when not in use. Minimize exposure to air and light.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Peracetic acid (79-21-0)

EU	IOELV TWA (mg/m ³)	1 mg/m ³
Germany	TRGS 910 Acceptable concentration notes	
Netherlands	MAC C (mg/m ³)	1 mg/m ³

Acetic acid (64-19-7)

EU	Local name	Acetic acid
EU	IOELV TWA (mg/m ³)	25 mg/m ³
EU	IOELV TWA (ppm)	10 ppm
EU	IOELV STEL (mg/m ³)	50 mg/m ³
EU	IOELV STEL (ppm)	20 ppm
EU	Regulatory reference	COMMISSION DIRECTIVE (EU) 2017/164
Belgium	Local name	Acide acétique # Azijnzuur
Belgium	Limit value (mg/m ³)	25 mg/m ³
Belgium	Limit value (ppm)	10 ppm
Belgium	Short time value (mg/m ³)	38 mg/m ³
Belgium	Short time value (ppm)	15 ppm
Belgium	Regulatory reference	Koninklijk besluit/Arrêté royal 02/09/2018
France	VLE (mg/m ³)	25 mg/m ³
France	VLE (ppm)	10 ppm
Germany	TRGS 900 Local name	Essigsäure
Germany	Occupational exposure limit value (mg/m ³)	25 mg/m ³
Germany	Occupational exposure limit value (ppm)	10 ppm
Germany	Limitation of exposure peaks (mg/m ³)	50 mg/m ³
Germany	Limitation of exposure peaks (ppm)	20 ppm
Germany	Limitation of exposure peaks	2(l)
Germany	TRGS 900 Remark	DFG;EU;Y
Germany	TRGS 900 Regulatory reference	TRGS900
Germany	TRGS 910 Acceptable concentration notes	
Latvia	OEL TWA (mg/m ³)	25 mg/m ³ (8h)
Latvia	OEL TWA (ppm)	10 ppm (8h)
United Kingdom	Local name	Acetic acid
United Kingdom	WEL TWA (mg/m ³)	25 mg/m ³
United Kingdom	WEL TWA (ppm)	10 ppm

Cid 2000 Pro

Safety Data Sheet

According to OSHA 29 CFR 1910.1200

Acetic acid (64-19-7)		
United Kingdom	WEL STEL (mg/m ³)	37 mg/m ³
United Kingdom	WEL STEL (ppm)	15 ppm
United Kingdom	Regulatory reference	EH40/2005 (Third edition, 2018). HSE
USA - ACGIH	ACGIH TWA (mg/m ³)	25 mg/m ³
USA - ACGIH	ACGIH TWA (ppm)	10 ppm
USA - ACGIH	ACGIH STEL (mg/m ³)	37 mg/m ³
USA - ACGIH	ACGIH STEL (ppm)	15 ppm

Hydrogen peroxide (7722-84-1)		
EU	Local name	Hydrogen peroxide
EU	IOELV TWA (mg/m ³)	1.4 mg/m ³
EU	IOELV TWA (ppm)	1 ppm
EU	Notes	(Ongoing)
EU	Regulatory reference	SCOEL Recommendations
Belgium	Local name	Hydrogène (peroxyde d') # Waterstofperoxide
Belgium	Limit value (mg/m ³)	1.4 mg/m ³
Belgium	Limit value (ppm)	1 ppm
Belgium	Remark (BE)	(peroxyde d')
Belgium	Regulatory reference	Koninklijk besluit/Arrêté royal 02/09/2018
Finland	HTP-arvo (8h) (mg/m ³)	1.4 mg/m ³
Finland	HTP-arvo (8h) (ppm)	1 ppm
Finland	HTP-arvo (15 min)	4.2 mg/m ³
Finland	HTP-arvo (15 min) (ppm)	3 ppm
France	VME (mg/m ³)	1.5 mg/m ³
France	VME (ppm)	1 ppm
Germany	TRGS 910 Acceptable concentration notes	
United Kingdom	Local name	Hydrogen peroxide
United Kingdom	WEL TWA (mg/m ³)	1.4 mg/m ³
United Kingdom	WEL TWA (ppm)	1 ppm
United Kingdom	WEL STEL (mg/m ³)	2.8 mg/m ³
United Kingdom	WEL STEL (ppm)	2 ppm
United Kingdom	Regulatory reference	EH40/2005 (Third edition, 2018). HSE
USA - ACGIH	ACGIH TWA (mg/m ³)	1.4 mg/m ³
USA - ACGIH	ACGIH TWA (ppm)	1 ppm

Peracetic acid (79-21-0)	
DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation	0.6 mg/m ³
Acute - local effects, dermal	0.12 % in mixture
Acute - local effects, inhalation	0.6 mg/m ³
Long-term - systemic effects, inhalation	0.6 mg/m ³
Long-term - local effects, inhalation	0.6 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, inhalation	0.6 mg/m ³
Acute - local effects, dermal	0.12 % in mixture

Cid 2000 Pro

Safety Data Sheet

According to OSHA 29 CFR 1910.1200

Peracetic acid (79-21-0)	
Acute - local effects, inhalation	0.3 mg/m ³
Long-term - systemic effects, inhalation	0.6 mg/m ³
Long-term - local effects, inhalation	0.6 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	0.000224 mg/l Assessment factor: 10
PNEC (Sediment)	
PNEC sediment (freshwater)	0.00018 mg/kg dwt
PNEC (Soil)	
PNEC soil	0.32 mg/kg dwt Assessment factor: 1000
PNEC (STP)	
PNEC sewage treatment plant	0.051 mg/l Assessment factor: 100
Acetic acid (64-19-7)	
DNEL/DMEL (Workers)	
Acute - local effects, inhalation	25 mg/m ³
Long-term - local effects, inhalation	25 mg/m ³
DNEL/DMEL (General population)	
Acute - local effects, inhalation	25 mg/m ³
Long-term - local effects, inhalation	25 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	3.058 mg/l Assessment factor: 100
PNEC aqua (marine water)	0.3058 mg/l Assessment factor: 100
PNEC aqua (intermittent, freshwater)	30.58 mg/l Assessment factor: 10
PNEC (Sediment)	
PNEC sediment (freshwater)	11.36 mg/kg dwt
PNEC sediment (marine water)	1.136 mg/kg dwt
PNEC (Soil)	
PNEC soil	0.47 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	85 mg/l Assessment factor: 10
Hydrogen peroxide (7722-84-1)	
DNEL/DMEL (Workers)	
Acute - local effects, inhalation	3 mg/m ³
Long-term - local effects, inhalation	1.4 mg/m ³
DNEL/DMEL (General population)	
Acute - local effects, inhalation	1.93 mg/m ³
Long-term - local effects, inhalation	0.21 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	0.0126 mg/l Assessment factor: 50
PNEC aqua (marine water)	0.0126 mg/l Assessment factor: 50
PNEC aqua (intermittent, freshwater)	0.0138 mg/l Assessment factor: 100
PNEC (Sediment)	
PNEC sediment (freshwater)	0.047 mg/kg dwt
PNEC sediment (marine water)	0.047 mg/kg dwt

Cid 2000 Pro

Safety Data Sheet

According to OSHA 29 CFR 1910.1200

Hydrogen peroxide (7722-84-1)

PNEC (Soil)

PNEC soil 0.0023 mg/kg dwt

PNEC (STP)

PNEC sewage treatment plant 4.66 mg/l Assessment factor: 100

8.2. Exposure controls

Appropriate engineering controls:

Local exhaust and general ventilation must be adequate to meet exposure standards.

Personal protective equipment:

Dust/aerosol mask. Gloves. Protective clothing.

Materials for protective clothing:

Condition	Material	Standard
Good resistance:		EN14605:2005+A1:2009

Hand protection:

Wear suitable gloves resistant to chemical penetration

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Reusable gloves	Polyvinylchloride (PVC)	6 (> 480 minutes)	0.5	2 (< 1.5)	EN ISO 374

Eye protection:

Chemical goggles or face shield with safety glasses

Type	Use	Characteristics	Standard
Safety glasses, Safety goggles, Face shield	Droplet	Clear, Plastic.	EN 166

Skin and body protection:

Wear suitable protective clothing

Type	Standard
	EN14605:2005+A1:2009

Respiratory protection:

Appropriate dust or mist respirator should be used if airborne particles are generated when handling this material

Device	Filter type	Condition	Standard
Full face mask	ABEK, Type P2	Protection for Liquid particles, Vapour protection, Long term exposure	EN 14387

Personal protective equipment symbol(s):



Other information:

When using do not eat, drink or smoke. Provide local exhaust or general room ventilation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear.
Colour	: Colourless.
Odour	: Pungent.
Odour threshold	: No data available
pH	: ≈ 3.5 (1%)

Cid 2000 Pro

Safety Data Sheet

According to OSHA 29 CFR 1910.1200

Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: - 30 °C
Freezing point	: No data available
Boiling point	: 118 °C
Flash point	: 100 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: ≥ 60 °C
Flammability (solid, gas)	: No data available
Vapour pressure	: 27 hPa
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: ≈ 1.11 kg/l
Solubility	: Water: 100 %
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts violently with: combustibles.

10.2. Chemical stability

No additional information available

10.3. Possibility of hazardous reactions

None under normal conditions.

10.4. Conditions to avoid

heat.

10.5. Incompatible materials

Avoid contact with : acids. Alkaline mixture. Reducing agents. metals. Organic compounds.

10.6. Hazardous decomposition products

May release : Oxygen.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Harmful if swallowed or in contact with skin.

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Harmful if inhaled.

ATE CLP (oral)	500 mg/kg bodyweight
ATE CLP (gases)	4500 ppmv/4h
ATE CLP (vapours)	11 mg/l/4h
ATE CLP (dust,mist)	1.5 mg/l/4h

Peracetic acid (79-21-0)

LD50 dermal rabbit	1147 mg/kg (5%, PAA mixture)
LC50 inhalation rat (mg/l)	4h 4080 mg/m ³ Aerosol, (5% PAA mixture)

Acetic acid (64-19-7)

LD50 oral rat	3310 mg/kg
---------------	------------

Hydrogen peroxide (7722-84-1)

LD50 oral rat	1193 – 1270 mg/kg
LD50 dermal rabbit	> 2000 mg/kg

Cid 2000 Pro

Safety Data Sheet

According to OSHA 29 CFR 1910.1200

LC50 inhalation rat (mg/l)	> 0.17 mg/l/4h
Skin corrosion/irritation	: Causes severe skin burns. pH: ≈ 3.5 (1%)
Serious eye damage/irritation	: Assumed to cause serious eye damage pH: ≈ 3.5 (1%)
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause respiratory irritation.

Cid 2000 Pro

LOAEL (oral, rat)	ca. 950 mg/kg bodyweight
LOAEL (dermal, rat/rabbit)	> 12000 mg/kg bodyweight

STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Very toxic to aquatic life with long lasting effects.

Cid 2000 Pro

LC50 fish 1	(50-96h) 25 mg/l ca.
LC50 other aquatic organisms 1	(50-72h) 12 mg/l ca.
EC50 Daphnia 1	(48h) 10 mg/l ca.

Acetic acid (64-19-7)

LC50 fish 1	> 300 mg/l
EC50 Daphnia 1	> 300 mg/l
EC50 other aquatic organisms 1	> 300 mg/l
ErC50 (algae)	> 300 mg/l

Hydrogen peroxide (7722-84-1)

LC50 fish 1	37.4 mg/l 96h
EC50 Daphnia 1	7.7 mg/l 24h

12.2. Persistence and degradability

Cid 2000 Pro

Persistence and degradability	Biodegradable.
-------------------------------	----------------

12.3. Bioaccumulative potential

Cid 2000 Pro

Bioaccumulative potential	No indication of bioaccumulation potential.
---------------------------	---

Peracetic acid (79-21-0)

Partition coefficient n-octanol/water (Log Kow)	-0.26
---	-------

Acetic acid (64-19-7)

Partition coefficient n-octanol/water (Log Kow)	-0.17
---	-------

Cid 2000 Pro

Safety Data Sheet

According to OSHA 29 CFR 1910.1200

Hydrogen peroxide (7722-84-1)

Partition coefficient n-octanol/water (Log Pow) : -1.57

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
Waste treatment methods	: Dispose of this material and its container at hazardous or special waste collection point. Hazardous waste due to toxicity. Avoid release to the environment. Dispose in a safe manner in accordance with local/national regulations.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: When totally empty, containers are recyclable like any other packing. Dispose in a safe manner in accordance with local/national regulations. Avoid release to the environment.
Ecology - waste materials	: Avoid release to the environment. Hazardous waste due to toxicity.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR)	: UN 3149
UN-No. (IMDG)	: UN 3149
UN-No. (IATA)	: UN 3149
UN-No. (ADN)	: UN 3149
UN-No. (RID)	: UN 3149

14.2. UN proper shipping name

Proper Shipping Name (ADR)	: HYDROGEN PEROXIDE AND PEROXYACETIC ACID MIXTURE STABILIZED
Proper Shipping Name (IMDG)	: HYDROGEN PEROXIDE AND PEROXYACETIC ACID MIXTURE STABILIZED
Proper Shipping Name (IATA)	: Hydrogen peroxide and peroxyacetic acid mixture stabilized
Proper Shipping Name (ADN)	: HYDROGEN PEROXIDE AND PEROXYACETIC ACID MIXTURE, STABILIZED
Proper Shipping Name (RID)	: HYDROGEN PEROXIDE AND PEROXYACETIC ACID MIXTURE, STABILIZED
Transport document description (ADR)	: UN 3149 HYDROGEN PEROXIDE AND PEROXYACETIC ACID MIXTURE STABILIZED, 5.1 (8), II, (E), ENVIRONMENTALLY HAZARDOUS
Transport document description (IMDG)	: UN 3149 HYDROGEN PEROXIDE AND PEROXYACETIC ACID MIXTURE STABILIZED, 5.1 (8), II, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS
Transport document description (IATA)	: UN 3149 Hydrogen peroxide and peroxyacetic acid mixture stabilized, 5.1, II, ENVIRONMENTALLY HAZARDOUS
Transport document description (ADN)	: UN 3149 HYDROGEN PEROXIDE AND PEROXYACETIC ACID MIXTURE, STABILIZED, 5.1 (8), II, ENVIRONMENTALLY HAZARDOUS
Transport document description (RID)	: UN 3149 HYDROGEN PEROXIDE AND PEROXYACETIC ACID MIXTURE, STABILIZED, 5.1 (8), II, ENVIRONMENTALLY HAZARDOUS

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR)	: 5.1 (8)
Danger labels (ADR)	: 5.1, 8



IMDG

Transport hazard class(es) (IMDG)	: 5.1 (8)
Danger labels (IMDG)	: 5.1, 8

Cid 2000 Pro

Safety Data Sheet

According to OSHA 29 CFR 1910.1200



IATA

Transport hazard class(es) (IATA) : 5.1 (8)

Danger labels (IATA) : 5.1, 8



ADN

Transport hazard class(es) (ADN) : 5.1 (8)

Danger labels (ADN) : 5.1, 8



RID

Transport hazard class(es) (RID) : 5.1 (8)

Danger labels (RID) : 5.1, 8



14.4. Packing group

Packing group (ADR) : II

Packing group (IMDG) : II

Packing group (IATA) : II

Packing group (ADN) : II

Packing group (RID) : II

14.5. Environmental hazards

Dangerous for the environment : Yes

Marine pollutant : Yes

Other information : Clean up even minor leaks or spills, if possible, without unnecessary risk

14.6. Special precautions for user

Special transport precautions : Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency, No naked flames, sparks, and do not smoke, Keep public away from danger area, NOTIFY POLICE AND FIRE BRIGADE IMMEDIATELY

Overland transport

Classification code (ADR) : OC1

Special provisions (ADR) : 196, 553

Limited quantities (ADR) : 1I

Excepted quantities (ADR) : E2

Packing instructions (ADR) : P504, IBC02

Special packing provisions (ADR) : PP10, B5

Mixed packing provisions (ADR) : MP15

Portable tank and bulk container instructions (ADR) : T7

Portable tank and bulk container special provisions (ADR) : TP2, TP6, TP24

Tank code (ADR) : L4BV(+)

Cid 2000 Pro

Safety Data Sheet

According to OSHA 29 CFR 1910.1200

Tank special provisions (ADR)	: TU3, TC2, TE8, TE11, TT1
Vehicle for tank carriage	: AT
Transport category (ADR)	: 2
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV24
Hazard identification number (Kemler No.)	: 58
Orange plates	:



Tunnel restriction code (ADR)	: E
EAC code	: 2P

Transport by sea

Special provisions (IMDG)	: 196
Limited quantities (IMDG)	: 1 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P504
Special packing provisions (IMDG)	: PP10
IBC packing instructions (IMDG)	: IBC02
IBC special provisions (IMDG)	: B5
Tank instructions (IMDG)	: T7
Tank special provisions (IMDG)	: TP2, TP6, TP24
EmS-No. (Fire)	: F-H
EmS-No. (Spillage)	: S-Q
Stowage category (IMDG)	: D
Stowage and handling (IMDG)	: SW1
Segregation (IMDG)	: SG16, SG59, SG72
MFAG-No	: 140

Air transport

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y540
PCA limited quantity max net quantity (IATA)	: 0.5L
PCA packing instructions (IATA)	: 550
PCA max net quantity (IATA)	: 1L
CAO packing instructions (IATA)	: 554
CAO max net quantity (IATA)	: 5L
Special provisions (IATA)	: A96
ERG code (IATA)	: 5C

Inland waterway transport

Classification code (ADN)	: OC1
Special provisions (ADN)	: 196, 553
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E2
Equipment required (ADN)	: PP, EP
Number of blue cones/lights (ADN)	: 0

Rail transport

Classification code (RID)	: OC1
Special provisions (RID)	: 196, 553
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E2
Packing instructions (RID)	: P504, IBC02
Special packing provisions (RID)	: PP10, B5
Mixed packing provisions (RID)	: MP15
Portable tank and bulk container instructions (RID)	: T7
Portable tank and bulk container special provisions (RID)	: TP2, TP6, TP24
Tank codes for RID tanks (RID)	: L4BV(+)

Cid 2000 Pro

Safety Data Sheet

According to OSHA 29 CFR 1910.1200

Special provisions for RID tanks (RID)	: TU3, TC2, TE8, TE11, TT1
Transport category (RID)	: 2
Special provisions for carriage - Loading, unloading and handling (RID)	: CW24
Colis express (express parcels) (RID)	: CE6
Hazard identification number (RID)	: 58

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

California Cleaning Product Right to Know Act of 2017 (SB 258)

Component	CAS-No.	Function	List(s)
Water	7732-18-5	Diluent	Not Applicable
Hydrogen Peroxide	7722-84-1	Brightener	Not Applicable
Acetic Acid	64-19-7	Buffer	Not Applicable
Ethaneperoxyic Acid	79-21-0	Cleaning Agent	Not Applicable
Chelating Agent	Withheld	Stabilizer	Not Applicable

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Other information : DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.

Classification according to Regulation (EC) No. 1272/2008 [CLP]:

Org. Perox. D	H242
Acute Tox. 4 (Oral)	H302
Acute Tox. 4 (Inhalation)	H332
Skin Corr. 1A	H314
STOT SE 3	H335
Aquatic Chronic 1	H410

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4

Cid 2000 Pro

Safety Data Sheet

According to OSHA 29 CFR 1910.1200

Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Flam. Liq. 3	Flammable liquids, Category 3
Org. Perox. D	Organic Peroxides, Type D
Ox. Liq. 1	Oxidising Liquids, Category 1
Skin Corr. 1A	Skin corrosion/irritation, Category 1A
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H226	Flammable liquid and vapour.
H242	Heating may cause a fire.
H271	May cause fire or explosion; strong oxidiser.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

SDS_U

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.